



15,3 m	17 m	18 m	11,8 m	13,5 m	L1	L2	W1	W2	W3
330 kg*	230 kg	120 kg	330 kg*	120/230 kg	5945 mm	7095 mm	5230 mm	4435 mm	3640 mm

BI-ENERGY
Diesel+AC



Model	Wheel Config	Height (m)	Reach (m)	Load (kg)	Rotation (°)	Swing (°)	Platform (cm)	Rotation (°)	Reach (m)	Stability (%)	Speed (km/h)	Weight (kg)	Capacity (kN)	Capacity (kN/m²)	Capacity (kN/m²)
XTJ 43⁺/C	🚶🚶🚶	43 m	18 m	330 kg*	170°	660°	240x70 cm	90°+80°	3,64-5,23 m	23%	2 km/h	10900 kg	75 kN	3,51 kN/m²	5,33 kN/m²
XTJ 43⁺/R	🚶🚶	43 m	18 m	330 kg*	170°	660°	240x70 cm	90°+80°	3,64-5,23 m	23%	1 km/h	10900 kg	75 kN	3,51 kN/m²	5,25 kN/m²

Available version:

- BI-ENERGY (DIESEL+AC)
- ECO (DC+AC)
- HYBRID (DIESEL+DC)

Characteristics and technical data are informative only and subjected to change without notice.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

Palazzani Industrie S.p.A.
Via del Pavione, 4 - 25050 - Paderno F.C. (BS) - Italy
Tel. (+39) 0306857073
platforms@palazzani.it
www.palazzani.it